

-  **EQUILIBRATRICI ELETTRONICHE COMPUTERIZZATE**
-  **ELECTRONIC WHEEL BALANCERS WITH MICROPROCESSOR**
-  **EQUILIBREUSES ELECTRONIQUES A MICROPROCESSEUR**
-  **EQUILIBRADORAS ELECTRÓNICAS CON MICROPROCESADOR**

S4140

TOUCH SCREEN



Optional on S4140R series

LED LIGHT



Illuminatori led
Led light
Lampes a led
Luz led

LASER POINTER (S)

S4140WSP - WS - RSP - RS




EXTERNAL POSITION



INTERNAL POSITION

SONAR (W)

S4140WSP - WS - WP - W



GAR 353

QUICK PROGRAM SELECTION



ALUS
ALUS1
ALUS2
STAT
STAT1
STAT2
DYNAMIC




Sono selezionabili 7 programmi semplicemente con l'utilizzo del tastatore automatico.

7 programs can be selected by simply using automatic internal data gauge.

7 programmes peuvent être sélectionnés en utilisant simplement la tige interne automatique.


7 programas pueden ser seleccionados por el simple uso de el palpador interno automático.



MODEL	Pneumatic locking system	Manual locking system	S=Laser Pointer	Led light	W=Sonar width dimension	GAR264 Wheel width gauge	GAR266 Wheel width gauge	Touch screen
								
S4140 Series 8 models	S4140WSP	STANDARD	-	STANDARD	STANDARD	-	-	OPTION VARGMONTS41
	S4140WS	-	STANDARD	STANDARD	STANDARD	-	-	OPTION VARGMONTS41
	S4140WP	STANDARD	-	-	STANDARD	-	-	OPTION VARGMONTS41
	S4140W	-	STANDARD	-	STANDARD	-	-	OPTION VARGMONTS41
	S4140RSP	STANDARD	-	STANDARD	-	STANDARD	-	OPTION VARGMONTS41
	S4140RS	-	STANDARD	STANDARD	-	STANDARD	-	OPTION VARGMONTS41
	S4140RP	STANDARD	-	-	STANDARD	-	STANDARD	OPTION VARGMONTS41
	S4140R	-	STANDARD	-	STANDARD	-	STANDARD	OPTION VARGMONTS41

AUTOMATIC WIDTH DIMENSION - INCLUDED

GAR 353 SONAR
S4140 **WSP** - **WS** - **WP** - **W**




GAR 264
S4140 **RSP** - **RS**



GAR 266
S4140 **RP** - **R**

Calibro larghezza
External data
gauge
Tige externe
Palpador externo



AUTOMATIC DISTANCE + DIAMETER MEASUREMENT





ALU-S

3 Programmi ALU S automatici.
3 Automatic ALU S programs.
 3 Programmes ALU S automatiques.
3 Programas ALU S automáticos.



SPOKE

Programma peso nascosto
Hidden weight program
 Programme masses cachées
 derrière les bâtons
Programa plomos escondidos



DYN



SPLIT

Programma split
SPLIT program
 Programme SPLIT
 Programa SPLIT



STATIC

Programma moto per equilibratura statica e dinamica.
Motorcycle program for static and dynamic balancing.
 Programme motos pour équilibrage statique et dynamique.
Programa moto para equilibrado estático y dinámico.

TOUCH SCREEN (Option)



S4141RSP

AIR LOCK (P)

S4140 WSP - WP - RSP - RP

Bloccaggio Pneumatico
 Pneumatic Locking
 Blocage Pneumatique
 Bloqueo Neumatico





EFFICIENZA E RISPARMIO
EFFICIENCY AND MONEY SAVING

Moderno sistema di azzeramento dello squilibrio per ridurre il consumo di pesi.

Modern balancing system to minimize wheel weights consumption.

Moderne système pour zérotagage du balourd pour réduire l'usure des poids.

Sistema moderno para poner a cero el desequilibrado y reducir el consumo de los plomos.

STANDARD



GAR 111
(Ø 44-112 mm)

GAR 108
(WSP - RSP - WP - RP)

GAR 101

OPTIONS



GAR327
Option for S4140W
Laser fisso
Fixed laser
Laser fixe
Laser fijo



GAR262
RUN-OUT




VARGMONT541
Touch screen



GAR316
Option only for GAR 264
Sensore run out ad ultrasuoni
Run out sonar



GAR 214/C
Option only for GAR 266
Sensore run out ad ultrasuoni
Run out sonar




GAR112
(Ø 95-132 mm)
Fuoristrada
Off-road vehicles
Véhicules tout-terrain
Todo terrenos



GAR131H
Flangia universale
Universal flange
Plateau universel
Plato universal



GAR132
Flangia di precisione
Precision flange
Plateau de précision
Plato de precisión



DATI TECNICI	TECHNICAL DATA	DONNEES TECHNIQUES	DATOS TÉCNICOS	
Diametro cerchio	Rim diameter	Diamètre de la jante	Diámetro de la llanta	10" ÷ 30" 10" ÷ 26" Automatic
Larghezza cerchio	Rim width	Largeur de la jante	Anchura de la llanta	1.5" ÷ 22"
Peso max ruota	Max wheel weight	Poids maxi de la roue	Peso máximo de la rueda	80 kg
Precisione equilibratura	Read-out accuracy	Précision d'équilibrage	Precisión de equilibrado	1g
Tempo di ciclo	Cycle time	Durée du cycle	Tiempo de medida	6 sec
Velocità di rotazione (giri/min)	Rotation speed (rpm)	Vitesse de rotation tours/min	Velocidad de rotación vueltas/min.	<100
Alimentazione	Power supply	Alimentation	Motor monofásico	110-230 V 50-60 / 1ph



Officine Meccaniche Sirio s.r.l. a s.u.

Via Brunelleschi, 9 - 44020 S. Giovanni di Ostellato (Ferrara) - Italy

Sirio Export: Tel. +39-051-6781604 - Fax +39-051-846349 - **Sirio Italia:** Tel. +39-051-6781511 - Fax +39-051-846349

e-mail: info@sirioequipment.com - www.sirioequipment.com

DSJ01U(05)

